






**Ceramic honeycomb catalyst having excellent thermal shock resistance**

**Patent number:** DE69706346T  
**Publication date:** 2002-06-13  
**Inventor:** KUMAZAWA KAZUHIKO (JP); IKESHIMA KOICHI (JP)  
**Applicant:** NGK INSULATORS LTD (JP)  
**Classification:**  
- **international:** *B01J35/04; B01J37/02; F01N3/28; F02B75/02; B01J35/00; B01J37/00; F01N3/28; F02B75/02; (IPC1-7): B01J35/04; B01J37/02; B01J37/08*  
- **european:** B01J35/04; B01J37/02C; F01N3/28B4  
**Application number:** DE19976006346T 19970401  
**Priority number(s):** JP19960076617 19960329

**Also published as:**

 EP0798042 (A1)  
 US5846899 (A1)  
 JP9262484 (A)  
 EP0798042 (B1)  
 CA2201090 (C)

**Report a data error here**

Abstract not available for DE69706346T

Abstract of corresponding document: **EP0798042**

A disclosed ceramic honeycomb catalyst having an excellent thermal shock resistance in which a carrier is coated on a ceramic honeycomb structural body, has a mean thermal expansion coefficient in a range from 40 to 800 DEG C of smaller than  $0.7 \times 10^{-6} / \text{DEG C}$ . Therefore, it is possible to obtain a ceramic honeycomb catalyst having an excellent thermal shock resistance in which a mechanical strength of a ceramic honeycomb structural body to which a carrier such as gamma -alumina is coated is not decreased and the carrier is not peeled off from the ceramic honeycomb structural body.

---

Data supplied from the **esp@cenet** database - Worldwide